NSN 5945-01-039-9852

Electrical Solenoid - Page 1 of 2

Body Style:Cylindrical frame



View Online at https://aerobasegroup.com/nsn/5945-01-039-9852

| Center To Center Distance Between Mounting Facilities Parallel To Length: |
|---|
| 1.062 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.062 inches |
| Body Diameter: |
| 1.250 inches |
| Body Length: |
| 2.000 inches |
| Unthreaded Mounting Hole Diameter: |
| Between 0.176 inches and 0.182 inches |
| Maximum Operating Temp: |
| 250.0 degrees fahrenheit |
| Mounting Base Width: |
| 1.375 inches |
| Inclosure Type: |
| Fully enclosed |
| Magnetic Coil Quantity: |
| 1 |
| Duty Type: |
| Continuous |
| Terminal Location: |
| Actuator end |
| Voltage Rating In Volts: |
| 28.0 dc |
| Mounting Facility Type And Quantity: |
| 4 unthreaded hole |
| Current Rating: |
| 0.650 amperes |
| Actuator Stroke Type: |
| Pull |
| Linear Force Delivered: |
| 8.00 pounds |
| Power Takeoff Connection Type: |
| Internal plunger |
| Energizing Stroke Maximum Length: |
| 0.025 inches |
| Mounting Facility Pattern: |
| Four position rectangular |
| Terminal Type And Quantity: |
| 2 wire lead |

NSN 5945-01-039-9852

Electrical Solenoid - Page 2 of 2



| C | ha | Ιf | 1 | ife | |
|---|-----|----|---|-------|--|
| • | ııe | | _ | .II C | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A134a0