NSN 5945-01-040-7082

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-040-7082

| Overall Length: |
|---|
| 1.180 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.000 inches single mounting facility |
| Overall Height: |
| 0.597 inches |
| Overall Width: |
| 0.410 inches |
| Environmental Protection: |
| Hermetic |
| Unthreaded Mounting Hole Diameter: |
| 0.096 inches single mounting facility |
| Winding Quantity: |
| 2 |
| Coil Quantity: |
| 2 |
| Winding Dc Resistance Rating: |
| 250.0 ohms all windings |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 2 unthreaded hole single mounting facility |
| Features Provided: |
| Polarized and latching contacts |
| Mounting Facility Pattern: |
| In-line single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 2 pole, double throw, one position momentary |
| Time Delay: |
| 0.006 seconds fixed operate time |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 15.0 volts dc 25 degrees celsius all windings |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 500.0 milliamperes dc resistive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 28.0 dc |
| Precious Material And Location: |
| Terminals gold |
| Precious Material: |
| Gold |
| Terminal Type And Quantity: |

10 pin all functions

NSN 5945-01-040-7082

Electromagnetic Relay - Page 2 of 2



| _ | | | | | |
|----|---|---|----|----|----|
| ٠. | n | _ | I+ | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300