## NSN 5945-01-042-7382

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-042-7382

C	Overall Length:
1	1.180 inches
C	Center To Center Distance Between Mounting Facilities Parallel To Length:
1	.000 inches single mounting facility
C	Overall Height:
C	0.620 inches
C	Overall Width:
C	0.400 inches
E	Environmental Protection:
H	Hermetic
ι	Inthreaded Mounting Hole Diameter:
C	0.096 inches single mounting facility
F	Fragility Factor:
١	Moderately rugged
٧	Vinding Quantity:
1	
F	Purpose For Which Designed:
C	General
C	Coil Quantity:
1	
٧	Vinding Dc Resistance Rating:
6	30.0 ohms single winding and 770.0 ohms single winding
	Outy Type:
C	Continuous
A	Arc Quenching Method:
A	Air
Ν	Mounting Facility Type And Quantity:
2	2 unthreaded hole single mounting facility
S	Storage Type:
c	General purpose warehouse

#### **Mounting Facility Pattern:**

In-line single mounting facility

### Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

#### Time Delay:

0.003 seconds fixed release time

#### **Operating Voltage Rating And Type At Specificationified Temp:**

26.0 volts dc 25 degrees celsius single winding

#### Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac resistive load and 2.0 amperes dc resistive load

#### **Main Contact Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

# NSN 5945-01-042-7382

Electromagnetic Relay - Page 2 of 2



Energizing	Element	Power	Rating:
------------	---------	-------	---------

175.0 milliwatts

**Terminal Type And Quantity:** 

8 pin all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300