NSN 5945-01-046-5145

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-046-5145

Overall Length:
0.880 inches
Overall Height:
0.490 inches
Overall Width:
0.480 inches
Case Material:
Metal
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
Contact Material:
Silver
Contact Surface Treatment:
Gold
End Application:
Support equipment for the c-130 aircraft, mx peacekeeper missile; emory s.Land class as
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
**** *********************************
1
1
1 Winding Dc Resistance Rating:
Winding Dc Resistance Rating: 218.0 ohms single winding
Winding Dc Resistance Rating: 218.0 ohms single winding Duty Type: Continuous
Winding Dc Resistance Rating: 218.0 ohms single winding Duty Type:
Winding Dc Resistance Rating: 218.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air
Winding Dc Resistance Rating: 218.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity:
Winding Dc Resistance Rating: 218.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility
Winding Dc Resistance Rating: 218.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type:
Winding Dc Resistance Rating: 218.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility
Winding Dc Resistance Rating: 218.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse
Winding Dc Resistance Rating: 218.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Cubic Measure:
Winding Dc Resistance Rating: 218.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Cubic Measure: 0.206 cubic inches
Winding Dc Resistance Rating: 218.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Cubic Measure: 0.206 cubic inches Nonpile-up Main Contact Arrangement:

Time Delay:

0.001 seconds fixed operate and release time

NSN 5945-01-046-5145

Electromagnetic Relay - Page 2 of 2



Operating Voltage Rating And Type At Specificationified Temp:

12.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac resistive load and 2.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

120.0 ac and 28.0 dc

Special Features:

Weapon system essential

Precious Material And Location:

Contacts silver and contact surfaces gold

Precious Material:

Silver and gold

Terminal Type And Quantity:

8 pin all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300