NSN 5945-01-051-1364

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-051-1364

Overall Length:

Between 6.375 inches and 6.499 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.490 inches single mounting facility and 2.510 inches single mounting facility

Overall Height:

6.187 inches

Overall Width:

Between 4.188 inches and 4.312 inches

Mounting Slot Width:

0.203 inches single mounting facility

Fragility Factor:

Moderately rugged

Frequency In Hertz:

Between 50.0 and 60.0

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

3 slotted hole single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

173.382 cubic inches

Mounting Facility Pattern:

Triangle single mounting facility

Nonpile-up Main Contact Arrangement:

3 pole, single throw, normally open, momentary action

Nonpile-up Auxiliary Contact Arrangement:

3 pole, single throw, normally open, momentary action

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

4.615 inches single mounting facility and 4.635 inches single mounting facility

Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

60.0 amperes ac resistive load

NSN 5945-01-051-1364

Electromagnetic Relay - Page 2 of 2



115.0 ac

Auxiliary Contact Load Current Rating At Maximum Rated Voltage:

60.0 amperes ac resistive load

Terminal Type And Quantity:

3 screw energizing element

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300