

View Online at <https://aerobasegroup.com/nsn/5945-01-051-3903>

**Overall Length:**

5.000 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

4.620 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.380 inches single mounting facility

**Overall Height:**

2.970 inches

**Overall Width:**

4.000 inches

**Environmental Protection:**

Fungus proof and humidity proof and salt spray resistant

**Unthreaded Mounting Hole Diameter:**

0.203 inches single mounting facility

**Frequency In Hertz:**

Between 50.0 and 60.0

**Winding Quantity:**

1

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

267.0 ohms single winding

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

4 unthreaded hole single mounting facility

**Mounting Facility Pattern:**

Rectangular single mounting facility

**Nonpile-up Main Contact Arrangement:**

6 pole, double throw, one position momentary

**Time Delay:**

0.03 seconds fixed operate and release time

**Operating Voltage Rating And Type At Specificationified Temp:**

120.0 volts ac 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

15.0 amperes ac resistive load

**Main Contact Maximum Voltage Rating In Volts:**

250.0 ac

**Special Features:**

6pdt reversing contactor with one set of contacts making before other five, unit shall have mechanical interlock

**Terminal Type And Quantity:**

20 pin all functions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03300