

View Online at <https://aerobasegroup.com/nsn/5945-01-051-3903>

Overall Length:

5.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.620 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.380 inches single mounting facility

Overall Height:

2.970 inches

Overall Width:

4.000 inches

Environmental Protection:

Fungus proof and humidity proof and salt spray resistant

Unthreaded Mounting Hole Diameter:

0.203 inches single mounting facility

Frequency In Hertz:

Between 50.0 and 60.0

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

267.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

6 pole, double throw, one position momentary

Time Delay:

0.03 seconds fixed operate and release time

Operating Voltage Rating And Type At Specificationified Temp:

120.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

15.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

250.0 ac

Special Features:

6pdt reversing contactor with one set of contacts making before other five, unit shall have mechanical interlock

Terminal Type And Quantity:

20 pin all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300