NSN 5945-01-052-1413

Electromagnetic Relay - Page 1 of 2

6 screw all functions



View Online at https://aerobasegroup.com/nsn/5945-01-052-1413

| Overall Length: |
|---|
| 4.250 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.500 inches single mounting facility |
| Overall Height: |
| 3.188 inches |
| Overall Width: |
| 3.188 inches |
| Mounting Slot Width: |
| 0.138 inches single mounting facility |
| Contact Material: |
| Silver |
| Frequency In Hertz: |
| Between 50.0 and 60.0 |
| Winding Quantity: |
| 2 |
| Coil Quantity: |
| 2 |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 3 slotted hole single mounting facility |
| Features Provided: |
| Latching contacts |
| Mounting Facility Pattern: |
| Triangle single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 1 pole, single throw, normally open, momentary action and 1 pole, single throw, normally closed, momentary action |
| Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: |
| 2.625 inches single mounting facility |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 300.0 volts ac 25 degrees celsius second winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 8.0 amperes ac resistive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 230.0 ac |
| Precious Material And Location: |
| Contacts silver |
| Precious Material: |
| Silver |
| Terminal Type And Quantity: |

NSN 5945-01-052-1413

Electromagnetic Relay - Page 2 of 2



| C | ha | Ιf | 1 | ife | |
|---|-----|----|---|-------|--|
| • | ııe | | _ | .II C | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300