NSN 5945-01-052-1413

Electromagnetic Relay - Page 1 of 2

6 screw all functions



View Online at https://aerobasegroup.com/nsn/5945-01-052-1413

Overall Length:
4.250 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.500 inches single mounting facility
Overall Height:
3.188 inches
Overall Width:
3.188 inches
Mounting Slot Width:
0.138 inches single mounting facility
Contact Material:
Silver
Frequency In Hertz:
Between 50.0 and 60.0
Winding Quantity:
2
Coil Quantity:
2
Duty Type:
Continuous
Mounting Facility Type And Quantity:
3 slotted hole single mounting facility
Features Provided:
Latching contacts
Mounting Facility Pattern:
Triangle single mounting facility
Nonpile-up Main Contact Arrangement:
1 pole, single throw, normally open, momentary action and 1 pole, single throw, normally closed, momentary action
Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:
2.625 inches single mounting facility
Operating Voltage Rating And Type At Specificationified Temp:
300.0 volts ac 25 degrees celsius second winding
Main Contact Load Current Rating At Maximum Rated Voltage:
8.0 amperes ac resistive load
Main Contact Maximum Voltage Rating In Volts:
230.0 ac
Precious Material And Location:
Contacts silver
Precious Material:
Silver
Terminal Type And Quantity:

NSN 5945-01-052-1413

Electromagnetic Relay - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300