

View Online at <https://aerobasegroup.com/nsn/5945-01-052-4397>

**Special Features:**

Operating conditions: pick-up: 18.0 to 22.0 volts dc ; drop-out: 7.0 volts dc ; input volts: 18.0 to 40.0 volts dc ; temperature range: minus 65.0 degrees fahrenheit to plus 160.0 degrees fahrenheit; current: 30.0 milliamps; pick-up delay time: 20.0 milliseconds, plus or minus 5.0 milliseconds; loading conditions: current: 1.0 ampere continuous; 7.0 amperes for 50.0 milliseconds; voltage drop: 2.0 volts dc at 7.0 amps inductive; leakage current: 30.0 milliamps; peak inverse voltage: 400.0 volts ; contact arrangement: spst normally open; coil quantity: 1; winding quantity: 1; terminals: 3 threaded studs; dimensions: length 2.500 inches max; width 2.000 inches max; height 1.110 inches max; mounting facility: 0.156 diameter hole and a 0.290 diameter hole multiplied by 100.0 degrees to countersink (2 places); center to center distance between mounting facilities parallel to length: 1.750 inches

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A513k0