NSN 5945-01-054-6752

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-054-6752

| Overall Length: |
|--|
| 0.810 inches |
| Overall Height: |
| 0.617 inches |
| Overall Width: |
| 0.410 inches |
| Environmental Protection: |
| Hermetic |
| Winding Quantity: |
| 1 |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 160.0 ohms single winding |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 1 terminal single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 2 pole, double throw, one position momentary |
| Criticality Code Justification: |
| Feat |
| Time Delay: |
| 0.004 seconds fixed operate and release time |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 12.0 volts dc 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 300.0 milliamperes ac resistive load and 2.0 amperes dc resistive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 115.0 ac and 28.0 dc |
| Special Features: |
| Failure rate level 1.0 percent |
| Test Data Document: |
| 81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type And Quantity: |
| 8 pin all functions |
| Specification Data: |
| 81349-mil-r-39016/6 government specification |
| Shelf Life: |
| N/a |

--

Unit Of Measure:

NSN 5945-01-054-6752

Electromagnetic Relay - Page 2 of 2



Demilitarization:

No

Fiig:

A03300