

View Online at <https://aerobasegroup.com/nsn/5945-01-055-6661>

Overall Length:

1.718 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.625 inches single mounting facility

Overall Height:

1.015 inches

Mounting Slot Width:

0.150 inches single mounting facility

Environmental Protection:

Hermetic and shock resistant and vibration resistant

Frequency In Hertz:

400.0

Winding Quantity:

1

Coil Quantity:

1

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 slotted hole single mounting facility

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

3 pole, single throw, normally open, momentary action

Time Delay:

0.05 seconds fixed release time

Nonpile-up Auxiliary Contact Arrangement:

1 pole, double throw, one position momentary

Auxiliary Contact Maximum Voltage Rating In Volts:

200.0 ac and 28.0 dc

Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac motor load and 10.0 amperes dc motor load

Main Contact Maximum Voltage Rating In Volts:

200.0 ac and 28.0 dc

Auxiliary Contact Load Current Rating At Maximum Rated Voltage:

500.0 milliamperes ac lamp load and 500.0 milliamperes dc lamp load

Terminal Type And Quantity:

11 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03300