NSN 5945-01-058-1565

Electromagnetic Relay - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5945-01-058-1565 | | | |
|---|--|--|--|
| Overall Length: | | | |
| 3.440 inches | | | |
| Center To Center Distance Between Mounting Facilities Parallel To Length: | | | |
| 2.500 inches single mounting facility | | | |
| Center To Center Distance Between Mounting Facilities Parallel To Width: | | | |
| 2.000 inches single mounting facility | | | |
| Overall Height: | | | |
| 1.560 inches | | | |
| Overall Width: | | | |
| 2.380 inches | | | |
| Environmental Protection: | | | |
| Shock resistant and vibration resistant and hermetic | | | |
| Unthreaded Mounting Hole Diameter: | | | |
| 0.170 inches single mounting facility and 0.176 inches single mounting facility | | | |
| Fragility Factor: | | | |
| Moderately rugged | | | |
| Winding Quantity: | | | |
| 1 | | | |
| Purpose For Which Designed: | | | |
| General | | | |
| Coil Quantity: | | | |
| 1 | | | |
| Duty Type: | | | |
| Continuous | | | |
| Arc Quenching Method: | | | |
| Air | | | |
| Mounting Facility Type And Quantity: | | | |
| 4 unthreaded hole single mounting facility | | | |
| Storage Type: | | | |
| General purpose warehouse | | | |
| Mounting Facility Pattern: | | | |
| Rectangular single mounting facility | | | |
| Nonpile-up Main Contact Arrangement: | | | |
| 2 pole, double throw, one position momentary | | | |
| Operating Voltage Rating And Type At Specificationified Temp: | | | |
| 200.0 volts ac 25 degrees celsius single winding | | | |

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac resistive load and 2.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Terminal Type And Quantity:

10 wire hook all functions

NSN 5945-01-058-1565

Electromagnetic Relay - Page 2 of 2



| | Life: |
|--|-------|
| | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300