## NSN 5945-01-058-7996

Electromagnetic Relay - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5945-01-058-7996

Overall Length:  1.750 inches  Center To Center Distance Between Mounting Facilities Parallel To Length:  1.375 inches single mounting facility  Overall Height:  1.250 inches  Overall Width:  0.880 inches  Environmental Protection:  Dustproof  Unthreaded Mounting Hole Diameter:  0.125 inches single mounting facility  Winding Quantity:  1  Coil Quantity:  1  Winding Dc Resistance Rating:  2.4 kilohms single winding  Duty Type:  Continuous  Mounting Facility Type And Quantity:  2 unthreaded hole single mounting facility  Mounting Facility Pattern:  In-line single mounting facility  Operating Voltage Rating And Type At Specificationified Temp:  24.0 volts dc 25 degrees celsius single winding  Shelf Life:  N/a
1.375 inches single mounting facility  Overall Height: 1.250 inches  Overall Width: 0.880 inches  Environmental Protection: Dustproof  Unthreaded Mounting Hole Diameter: 0.125 inches single mounting facility  Winding Quantity: 1  Coil Quantity: 1  Winding Dc Resistance Rating: 2.4 kilohms single winding  Duty Type: Continuous  Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility  Mounting Facility Pattern: In-line single mounting facility  Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding  Shelf Life:
1.375 inches single mounting facility  Overall Height: 1.250 inches  Overall Width: 0.880 inches  Environmental Protection: Dustproof  Unthreaded Mounting Hole Diameter: 0.125 inches single mounting facility  Winding Quantity: 1  Coil Quantity: 1  Winding Dc Resistance Rating: 2.4 kilohms single winding  Duty Type: Continuous  Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility  Mounting Facility Pattern: In-line single mounting facility  Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding  Shelf Life:
Overall Height:  1.250 inches  Overall Width:  0.880 inches  Environmental Protection:  Dustproof  Unthreaded Mounting Hole Diameter:  0.125 inches single mounting facility  Winding Quantity:  1  Coil Quantity:  1  Winding Dc Resistance Rating:  2.4 kilohms single winding  Duty Type:  Continuous  Mounting Facility Type And Quantity:  2 unthreaded hole single mounting facility  Mounting Facility Pattern:  In-line single mounting facility  Operating Voltage Rating And Type At Specificationified Temp:  24.0 volts dc 25 degrees celsius single winding  Shelf Life:
Overall Width:  0.880 inches  Environmental Protection:  Dustproof  Unthreaded Mounting Hole Diameter:  0.125 inches single mounting facility  Winding Quantity:  1  Coil Quantity:  1  Winding Dc Resistance Rating:  2.4 kilohms single winding  Duty Type:  Continuous  Mounting Facility Type And Quantity:  2 unthreaded hole single mounting facility  Mounting Facility Pattern:  In-line single mounting facility  Operating Voltage Rating And Type At Specificationified Temp:  24.0 volts dc 25 degrees celsius single winding  Shelf Life:
0.880 inches  Environmental Protection:  Dustproof  Unthreaded Mounting Hole Diameter: 0.125 inches single mounting facility  Winding Quantity:  1  Coil Quantity: 1  Winding Dc Resistance Rating: 2.4 kilohms single winding  Duty Type:  Continuous  Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility  Mounting Facility Pattern: In-line single mounting facility  Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding  Shelf Life:
Environmental Protection:  Dustproof  Unthreaded Mounting Hole Diameter: 0.125 inches single mounting facility  Winding Quantity: 1  Coil Quantity: 1  Winding Dc Resistance Rating: 2.4 kilohms single winding  Duty Type: Continuous  Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility  Mounting Facility Pattern: In-line single mounting facility  Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding  Shelf Life:
Unthreaded Mounting Hole Diameter:  0.125 inches single mounting facility Winding Quantity:  1 Coil Quantity:  1 Winding Dc Resistance Rating: 2.4 kilohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Mounting Facility Pattern: In-line single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding Shelf Life:
Unthreaded Mounting Hole Diameter:  0.125 inches single mounting facility  Winding Quantity:  1  Coil Quantity:  1  Winding Dc Resistance Rating:  2.4 kilohms single winding  Duty Type:  Continuous  Mounting Facility Type And Quantity:  2 unthreaded hole single mounting facility  Mounting Facility Pattern:  In-line single mounting facility  Operating Voltage Rating And Type At Specificationified Temp:  24.0 volts dc 25 degrees celsius single winding  Shelf Life:
O.125 inches single mounting facility  Winding Quantity:  1  Coil Quantity:  1  Winding Dc Resistance Rating: 2.4 kilohms single winding  Duty Type:  Continuous  Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility  Mounting Facility Pattern:  In-line single mounting facility  Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding  Shelf Life:
Winding Quantity:  1 Coil Quantity:  1 Winding Dc Resistance Rating: 2.4 kilohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Mounting Facility Pattern: In-line single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding Shelf Life:
Coil Quantity:  1 Winding Dc Resistance Rating: 2.4 kilohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Mounting Facility Pattern: In-line single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding Shelf Life:
Coil Quantity:  1 Winding Dc Resistance Rating: 2.4 kilohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Mounting Facility Pattern: In-line single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding Shelf Life:
Winding Dc Resistance Rating:  2.4 kilohms single winding  Duty Type:  Continuous  Mounting Facility Type And Quantity:  2 unthreaded hole single mounting facility  Mounting Facility Pattern:  In-line single mounting facility  Operating Voltage Rating And Type At Specificationified Temp:  24.0 volts dc 25 degrees celsius single winding  Shelf Life:
Winding Dc Resistance Rating:  2.4 kilohms single winding  Duty Type:  Continuous  Mounting Facility Type And Quantity:  2 unthreaded hole single mounting facility  Mounting Facility Pattern:  In-line single mounting facility  Operating Voltage Rating And Type At Specificationified Temp:  24.0 volts dc 25 degrees celsius single winding  Shelf Life:
2.4 kilohms single winding  Duty Type: Continuous  Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility  Mounting Facility Pattern: In-line single mounting facility  Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding  Shelf Life:
Duty Type: Continuous  Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility  Mounting Facility Pattern: In-line single mounting facility  Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding  Shelf Life:
Continuous  Mounting Facility Type And Quantity:  2 unthreaded hole single mounting facility  Mounting Facility Pattern:  In-line single mounting facility  Operating Voltage Rating And Type At Specificationified Temp:  24.0 volts dc 25 degrees celsius single winding  Shelf Life:
Mounting Facility Type And Quantity:  2 unthreaded hole single mounting facility  Mounting Facility Pattern:  In-line single mounting facility  Operating Voltage Rating And Type At Specificationified Temp:  24.0 volts dc 25 degrees celsius single winding  Shelf Life:
2 unthreaded hole single mounting facility  Mounting Facility Pattern: In-line single mounting facility  Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding  Shelf Life:
Mounting Facility Pattern: In-line single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding Shelf Life:
In-line single mounting facility  Operating Voltage Rating And Type At Specificationified Temp:  24.0 volts dc 25 degrees celsius single winding  Shelf Life:
Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding Shelf Life:
24.0 volts dc 25 degrees celsius single winding  Shelf Life:
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A03300