## NSN 5945-01-063-1979

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-063-1979 **Overall Length:** 0.810 inches **Overall Height:** 0.617 inches Overall Width: 0.410 inches **Environmental Protection:** Hermetic

Winding Quantity:

**Coil Quantity:** 

Winding Dc Resistance Rating:

700.0 ohms single winding

**Duty Type:** 

Continuous

**Mounting Facility Type And Quantity:** 

1 plug-in terminal single mounting facility

**Nonpile-up Main Contact Arrangement:** 

2 pole, double throw, one position momentary

**Criticality Code Justification:** 

Feat

Time Delay:

0.004 seconds fixed operate and release time

Operating Voltage Rating And Type At Specificationified Temp:

26.5 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

100.0 milliamperes ac resistive load and 2.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

**Special Features:** 

Failure rate level 3.0

**Test Data Document:** 

81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:** 

8 pin all functions

**Specification Data:** 

81349-mil-r-39016/6 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5945-01-063-1979

Electromagnetic Relay - Page 2 of 2



Demilitarization:

No

Fiig:

A03300