

View Online at <https://aerobasegroup.com/nsn/5945-01-065-5793>

Overall Length:

Between 2.718 inches and 2.781 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.343 inches second mounting facility and 2.406 inches second mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.405 inches second mounting facility and 0.468 inches second mounting facility

Overall Height:

Between 3.968 inches and 4.031 inches

Overall Width:

Between 1.514 inches and 1.577 inches

Environmental Protection:

Dustproof

Unthreaded Mounting Hole Diameter:

0.138 inches second mounting facility

Fragility Factor:

Moderately rugged

Contact Material:

Silver

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Winding Dc Resistance Rating:

394.2 ohms single winding and 481.8 ohms single winding

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

6 unthreaded hole second mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

17.015 cubic inches

Mounting Facility Pattern:

Rectangular second mounting facility

Nonpile-up Main Contact Arrangement:

48 pole, double throw, one position momentary

Time Delay:

0.035 seconds fixed operate time

Operating Voltage Rating And Type At Specificationified Temp:

24.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

333.0 milliamperes ac resistive load and 1.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

120.0 ac and 28.0 dc

Precious Material And Location:

Contact surfaces gold and contact surfaces rhodium and contacts silver

Precious Material:

Gold and rhodium and silver

Terminal Type And Quantity:

146 tab, solder lug all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300