

View Online at <https://aerobasegroup.com/nsn/5945-01-065-5793>

**Overall Length:**

Between 2.718 inches and 2.781 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.343 inches second mounting facility and 2.406 inches second mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.405 inches second mounting facility and 0.468 inches second mounting facility

**Overall Height:**

Between 3.968 inches and 4.031 inches

**Overall Width:**

Between 1.514 inches and 1.577 inches

**Environmental Protection:**

Dustproof

**Unthreaded Mounting Hole Diameter:**

0.138 inches second mounting facility

**Fragility Factor:**

Moderately rugged

**Contact Material:**

Silver

**Winding Quantity:**

1

**Purpose For Which Designed:**

General

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

394.2 ohms single winding and 481.8 ohms single winding

**Duty Type:**

Continuous

**Arc Quenching Method:**

Air

**Mounting Facility Type And Quantity:**

6 unthreaded hole second mounting facility

**Storage Type:**

General purpose warehouse

**Cubic Measure:**

17.015 cubic inches

**Mounting Facility Pattern:**

Rectangular second mounting facility

**Nonpile-up Main Contact Arrangement:**

48 pole, double throw, one position momentary

**Time Delay:**

0.035 seconds fixed operate time

**Operating Voltage Rating And Type At Specificationified Temp:**

24.0 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

333.0 milliamperes ac resistive load and 1.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:**

120.0 ac and 28.0 dc

**Precious Material And Location:**

Contact surfaces gold and contact surfaces rhodium and contacts silver

**Precious Material:**

Gold and rhodium and silver

**Terminal Type And Quantity:**

146 tab, solder lug all functions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03300