NSN 5945-01-065-8705

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-065-8705

Overa	II I	en	ath:
Overa		.cii	uui.

Between 5.100 inches and 5.120 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.490 inches single mounting facility and 4.510 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.990 inches single mounting facility and 4.010 inches single mounting facility

Overall Height:

Between 4.420 inches and 4.440 inches

Overall Width:

Between 4.600 inches and 4.620 inches

Case Material:

Metal

Environmental Protection:

Dustproof

Unthreaded Mounting Hole Diameter:

0.213 inches single mounting facility and 0.228 inches single mounting facility

Fragility Factor:

Moderately rugged

Frequency In Hertz:

60.0

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Storage Type:

General purpose warehouse

Features Provided:

Coil voltage suppression

Cubic Measure:

105.025 cubic inches

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

3 pole, single throw, normally open, momentary action

NSN 5945-01-065-8705

Electromagnetic Relay - Page 2 of 2



		_	-	
Tin	^^	\mathbf{D}	121/	٠
	IIC.	De	ıav.	

0.09 seconds fixed release time

Nonpile-up Auxiliary Contact Arrangement:

1 pole, single throw, normally open, momentary action

Auxiliary Contact Maximum Voltage Rating In Volts:

115.0 ac and 50.0 dc

Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

60.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

440.0 ac

Auxiliary Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes ac resistive load and 5.0 amperes dc resistive load

Terminal Type And Quantity:

10 threaded stud all functions

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300