

View Online at <https://aerobasegroup.com/nsn/5945-01-066-6889>

Overall Length:

0.280 inches

Overall Diameter:

0.335 inches

Case Material:

Metal

Environmental Protection:

Hermetic

Fragility Factor:

Moderately rugged

Winding Quantity:

2

Coil Quantity:

2

Winding Dc Resistance Rating:

280.0 ohms all windings

Duty Type:

Continuous

Mounting Facility Type And Quantity:

1 terminal single mounting facility

Storage Type:

General purpose warehouse

Features Provided:

Latching contacts

Nonpile-up Main Contact Arrangement:

1 pole, double throw, one position momentary

Criticality Code Justification:

Feat

Time Delay:

0.0015 seconds fixed operate time

Operating Voltage Rating And Type At Specificationified Temp:

9.0 volts dc 25 degrees celsius all windings

Main Contact Load Current Rating At Maximum Rated Voltage:

100.0 milliamperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

28.0 dc

Special Features:

Failure rate level of 1.0 percent

Test Data Document:

81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

7 wire lead all functions

Specification Data:

81349-mil-r-39016/8 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300