## NSN 5945-01-068-0919

Electromagnetic Relay - Page 1 of 2

Overall Length: 0.930 inches Overall Height:



View Online at https://aerobasegroup.com/nsn/5945-01-068-0919

0.810 inches
Overall Width:
0.810 inches
Case Material:
Metal
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
Winding Quantity:
1
Coil Quantity:
1
Winding Dc Resistance Rating:
400.0 ohms single winding
Duty Type:
Continuous
Storage Type:
General purpose warehouse
Features Provided:
Coil voltage suppression and polarized
Nonpile-up Main Contact Arrangement:
3 pole, double throw, one position momentary
Operating Current Rating And Type:
81.0 milliamperes dc single winding
Time Delay:
0.006 seconds fixed operate and release time
Operating Voltage Rating And Type At Specificationified Temp:
28.0 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
2.0 amperes ac lamp load and 2.0 amperes dc lamp load
Main Contact Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Precious Material And Location:
Terminal surface gold
Precious Material:
Gold
Test Data Document:
81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## NSN 5945-01-068-0919

Electromagnetic Relay - Page 2 of 2



Terminal Type And Quantity:
11 pin all functions
Specification Data:
81349-mil-r-6106/24 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A03300