NSN 5945-01-068-0919

Electromagnetic Relay - Page 1 of 2

Overall Length: 0.930 inches Overall Height:



View Online at https://aerobasegroup.com/nsn/5945-01-068-0919

0.810 inches
Overall Width:
0.810 inches
Case Material:
Metal
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
Winding Quantity:
1
Coil Quantity:
1
Winding Dc Resistance Rating:
400.0 ohms single winding
Duty Type:
Continuous
Storage Type:
General purpose warehouse
Features Provided:
Coil voltage suppression and polarized
Nonpile-up Main Contact Arrangement:
3 pole, double throw, one position momentary
Operating Current Rating And Type:
81.0 milliamperes dc single winding
Time Delay:
0.006 seconds fixed operate and release time
Operating Voltage Rating And Type At Specificationified Temp:
28.0 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
2.0 amperes ac lamp load and 2.0 amperes dc lamp load
Main Contact Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Precious Material And Location:
Terminal surface gold
Precious Material:
Gold
Test Data Document:
81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

NSN 5945-01-068-0919

Electromagnetic Relay - Page 2 of 2



Terminal Type And Quantity:
11 pin all functions
Specification Data:
81349-mil-r-6106/24 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A03300