NSN 5945-01-070-6889

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-070-6889

| Overall Length |
|---|
| Overall Length: 3.688 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 3.250 inches single mounting facility |
| |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.688 inches single mounting facility |
| Overall Height: 3.156 inches |
| |
| Overall Width: |
| 2.422 inches |
| Mounting Slot Width: |
| 0.150 inches single mounting facility |
| Case Material: |
| Metal |
| Fragility Factor: |
| Moderately rugged |
| Winding Quantity: |
| |
| Purpose For Which Designed: |
| General |
| Coil Quantity: |
| |
| Winding Dc Resistance Rating: |
| 390.0 ohms single winding |
| Duty Type: |
| Continuous |
| Arc Quenching Method: |
| Air |
| Mounting Facility Type And Quantity: |
| 4 slotted hole single mounting facility |
| Storage Type: |
| General purpose warehouse |
| Cubic Measure: |
| 28.190 cubic inches |
| Mounting Facility Pattern: |
| Rectangular single mounting facility |
| Nonpile-up Main Contact Arrangement: |

Operating Voltage Rating And Type At Specificationified Temp: 220.0 volts ac 25 degrees celsius single winding

2 pole, single throw, normally open, momentary action

Main Contact Load Current Rating At Maximum Rated Voltage:

20.0 amperes ac resistive load and 20.0 amperes dc resistive load

NSN 5945-01-070-6889

Electromagnetic Relay - Page 2 of 2



| Main Contact Maximum Voltage Rating In Volts: | Main | Contact | Maximum | Voltage | Rating | In | Volts: |
|---|------|---------|---------|---------|--------|----|--------|
|---|------|---------|---------|---------|--------|----|--------|

115.0 ac and 28.0 dc

Terminal Type And Quantity:

6 pin all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300