NSN 5945-01-071-5230

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-071-5230

Overall Length:

Between 1.735 inches and 1.765 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.356 inches single mounting facility and 1.484 inches single mounting facility

Overall Height:

Between 1.218 inches and 1.238 inches

Overall Width:

Between 0.505 inches and 0.525 inches

Mounting Slot Width:

0.139 inches single mounting facility and 0.149 inches single mounting facility

Case Material:

Metal

Environmental Protection:

Hermetic

Fragility Factor:

Moderately rugged

Winding Quantity:

Purpose For Which Designed:

General

Coil Quantity:

Winding Dc Resistance Rating:

300.0 ohms single winding

Duty Type:

Continuous

Arc Quenching Method:

Mounting Facility Type And Quantity:

2 slotted hole single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

1.147 cubic inches

Mounting Facility Pattern:

In-line single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Operating Current Rating And Type:

120.0 milliamperes dc single winding

Time Delay:

0.01 seconds fixed operate and release time

NSN 5945-01-071-5230

Electromagnetic Relay - Page 2 of 2

Fiig: A03300

Mil-std (military Standard):

Mil-r-6106 spec.



Operating Voltage Rating And Type At Specificationified Temp:
28.0 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
2.0 amperes ac lamp load and 2.0 amperes dc lamp load
Main Contact Maximum Voltage Rating In Volts:
200.0 ac and 28.0 dc
Precious Material And Location:
Terminal surfaces gold
Precious Material:
Gold
Test Data Document:
81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
8 pin all functions
Specification Data:
96906-ms27247 government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No