## NSN 5945-01-072-3981

Reed Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-072-3981

Overall Length:
0.783 inches
Overall Height:
0.375 inches
Overall Width:
0.383 inches
Case Material:
Plastic
Fragility Factor:
Moderately rugged
End Application:
Kidd class ddg, kilauea class t-ae 26, landing craft air cushion (lcac), los angeles class ssn (688), virginia class cgn (41), nimitz class cvn,
sturgeon class ssn (637), ticonderoga class cg (47), spruance class dd (963), forrestal class cv
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
500.0 ohms single winding
Duty Type:
Continuous
Mounting Facility Type And Quantity:
1 plug-in terminal single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
0.112 cubic inches
Nonpile-up Main Contact Arrangement:
1 pole, single throw, normally open, momentary action
Criticality Code Justification:
Feat
Operating Voltage Rating And Type At Specificationified Temp:
5.0 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
500.0 milliamperes dc resistive load
Main Contact Maximum Voltage Rating In Volts:
100.0 dc
Special Features:

4 pin all functions

Weapon system essential

Terminal Type And Quantity:

## NSN 5945-01-072-3981

Reed Relay - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300