

View Online at <https://aerobasegroup.com/nsn/5945-01-075-4610>

Overall Length:

3.500 inches

Overall Diameter:

2.000 inches

Environmental Protection:

Shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.196 inches single mounting facility

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

120.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

6 unthreaded hole single mounting facility

Mounting Facility Pattern:

Circular single mounting facility

Nonpile-up Main Contact Arrangement:

1 pole, double throw, one position momentary

Time Delay:

0.025 seconds fixed operate time

Operating Voltage Rating And Type At Specificationified Temp:

26.5 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

25.0 amperes ac resistive load and 25.0 amperes dc resistive load

Test Data Document:

81349-mil-r-83725 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

5 tab, solder lug all functions

Specification Data:

81349-mil-r-83725/2 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03300