## NSN 5945-01-075-4610

Electromagnetic Relay - Page 1 of 1

**Fiig:** A03300



View Online at https://aerobasegroup.com/nsn/5945-01-075-4610

Overall Length:
3.500 inches
Overall Diameter:
2.000 inches
Environmental Protection:
Shock resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.196 inches single mounting facility
Winding Quantity:
1
Coil Quantity:
1
Winding Dc Resistance Rating:
120.0 ohms single winding
Duty Type:
Continuous
Mounting Facility Type And Quantity:
6 unthreaded hole single mounting facility
Mounting Facility Pattern:
Ciruclar single mounting facility
Nonpile-up Main Contact Arrangement:
1 pole, double throw, one position momentary
Time Delay:
0.025 seconds fixed operate time
Operating Voltage Rating And Type At Specificationified Temp:
26.5 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
25.0 amperes ac resistive load and 25.0 amperes dc resistive load
Test Data Document:
81349-mil-r-83725 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
5 tab, solder lug all functions
Specification Data:
81349-mil-r-83725/2 government specification
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No