

View Online at <https://aerobasegroup.com/nsn/5945-01-076-4463>

Overall Length:

6.520 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.437 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.687 inches single mounting facility

Overall Height:

5.380 inches

Overall Width:

6.190 inches

Unthreaded Mounting Hole Diameter:

0.218 inches single mounting facility

Winding Quantity:

1

Coil Quantity:

1

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Features Provided:

Polarized

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

3 pole, single throw, normally open, momentary action

Operating Current Rating And Type:

10.0 amperes dc single winding

Time Delay:

0.05 seconds fixed operate time

Nonpile-up Auxiliary Contact Arrangement:

3 pole, single throw, normally closed, momentary action and 4 pole, double throw, one position momentary

Auxiliary Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Operating Voltage Rating And Type At Specificationified Temp:

15.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

350.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac

Auxiliary Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes ac resistive load and 5.0 amperes dc resistive load

Terminal Type And Quantity:

26 screw all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300