# NSN 5945-01-078-9441

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-078-9441

**Overall Length:** 

1.343 inches

**Overall Height:** 

2.004 inches

Overall Width:

1.020 inches

Fragility Factor:

Moderately rugged

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Winding Dc Resistance Rating:

290.0 ohms single winding

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

14 plug-in terminal single mounting facility

Storage Type:

General purpose warehouse

**Features Provided:** 

Polarized

Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

### **Operating Current Rating And Type:**

110.0 milliamperes dc single winding

Time Delay:

0.02 seconds fixed release time

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac lamp load and 2.0 amperes dc lamp load

## Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

**Precious Material And Location:** 

Terminal surfaces gold

**Precious Material:** 

Gold

## NSN 5945-01-078-9441

Electromagnetic Relay - Page 2 of 2



#### **Test Data Document:**

81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
2 pin energizing element
Specification Data:
81349-mil-r-6106/2 government specification
Shelf Life:
N/a
Unit Of Measure:
-Demilitarization:
No
Fig:
A03300