NSN 5945-01-079-0347

Electromagnetic Relay - Page 1 of 2

No



/iew Online at https://aerobasegroup.com/nsn/5945-01-079-0347	
Overall Length:	
.230 inches	
Overall Diameter:	
.130 inches	
invironmental Protection:	
Dustproof	
Inthreaded Mounting Hole Diameter:	
.141 inches single mounting facility	
Vinding Quantity:	
Coil Quantity:	
Vinding Dc Resistance Rating:	
00.0 ohms single winding	
Duty Type:	
Continuous	
Iounting Facility Type And Quantity:	
unthreaded hole single mounting facility	
Iounting Facility Pattern:	
Ciruclar single mounting facility	
Ionpile-up Main Contact Arrangement:	
pole, double throw, one position momentary	
ïme Delay:	
.01 seconds fixed operate and release time	
Operating Voltage Rating And Type At Specificationified Temp:	
6.5 volts dc 25 degrees celsius all windings	
Iain Contact Load Current Rating At Maximum Rated Voltage:	
.0 amperes ac resistive load and 8.0 amperes dc resistive load	
Iain Contact Maximum Voltage Rating In Volts:	
000.0 ac and 2000.0 dc	
est Data Document:	
1349-mil-r-83725 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specifi	cation
prmat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certai	
nvironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
erminal Type And Quantity:	
tab, solder lug all functions	
Specification Data:	
1349-mil-r-83725/3 government specification	
Shelf Life:	
I/a	
Init Of Measure:	
Demilitarization:	

NSN 5945-01-079-0347

Electromagnetic Relay - Page 2 of 2

Fiig: A03300

