NSN 5945-01-079-8936

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-079-8936

| view Online at https://aerobasegroup.com/nsn/5945-01-079-6936 |
|---|
| Thread Class: |
| 2a single mounting facility |
| Overall Length: |
| 1.156 inches |
| Overall Height: |
| 1.406 inches |
| Overall Width: |
| 0.734 inches |
| Case Material: |
| Plastic |
| Environmental Protection: |
| Dustproof |
| Contact Material: |
| Gold and silver |
| Winding Quantity: |
| 1 |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 2.5 kilohms single winding |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 1 threaded stud single mounting facility |
| Thready Qty Per Inch (tpi): |
| 48 single mounting facility |
| Thread Size: |
| 0.099 inches single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 4 pole, double throw, one position momentary |
| Operating Current Rating And Type: |
| 9.1 milliamperes dc single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 3.0 amperes ac resistive load and 3.0 amperes dc resistive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 115.0 ac and 28.0 dc |
| Precious Material And Location: |
| Contact gold and c0ntact silver |
| Precious Material: |
| Gold and silver |

Thread Series Designator: Unc single mounting facility

NSN 5945-01-079-8936

Electromagnetic Relay - Page 2 of 2



| Terminal Type A | and Quantity | /: |
|-----------------|--------------|-----------|
|-----------------|--------------|-----------|

14 tab, solder lug all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300