# NSN 5945-01-079-9599

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-079-9599

## **Overall Length:**

2.187 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

1.844 inches single mounting facility

#### **Overall Height:**

2.015 inches

#### **Overall Width:**

1.031 inches

#### **Case Material:**

Metal

#### **Environmental Protection:**

Hermetic

#### **Unthreaded Mounting Hole Diameter:**

0.147 inches single mounting facility

#### **Fragility Factor:**

#### Moderately rugged

Frequency In Hertz:

400.0

#### Winding Quantity:

1

#### **Purpose For Which Designed:**

General

#### **Coil Quantity:**

1

## Duty Type:

Continuous

## Arc Quenching Method:

Air

## Mounting Facility Type And Quantity:

2 unthreaded hole single mounting facility

## Storage Type:

General purpose warehouse

## **Cubic Measure:**

4.543 cubic inches

## Mounting Facility Pattern:

In-line single mounting facility

## Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

## Time Delay:

0.05 seconds fixed release time

## Operating Voltage Rating And Type At Specificationified Temp:

440.0 volts ac 25 degrees celsius single winding

## NSN 5945-01-079-9599

Electromagnetic Relay - Page 2 of 2



Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac resistive load and 10.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Terminal Type And Quantity:

8 pin all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300