NSN 5945-01-081-4710

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-081-4710

| Thread Class: |
|--|
| 2a single mounting facility |
| Overall Length: |
| 2.190 inches |
| Overall Height: |
| 2.440 inches |
| Overall Width: |
| 1.250 inches |
| Environmental Protection: |
| Hermetic |
| Center To Center Distance Between Mounting Facilities Parallel To Height: |
| 1.250 inches single mounting facility |
| Frequency In Hertz: |
| 400.0 |
| Winding Quantity: |
| 1 |
| Coil Quantity: |
| 1 |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 3 threaded stud single mounting facility |
| Thready Qty Per Inch (tpi): |
| 32 single mounting facility |
| Thread Size: |
| 0.138 inches single mounting facility |
| Mounting Facility Pattern: |
| Triangle single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 1 pole, double throw, one position momentary |
| Time Delay: |
| 0.10 seconds fixed release time |
| Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: |
| 0.625 inches single mounting facility |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 208.0 volts ac 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 250.0 milliamperes ac resistive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 208.0 ac |
| Thread Series Designator: |
| Unc single mounting facility |

NSN 5945-01-081-4710

Electromagnetic Relay - Page 2 of 2



| Terminal T | Type And | Quantity: |
|------------|----------|-----------|
|------------|----------|-----------|

5 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300