NSN 5945-01-081-5478

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-081-5478

view Orilline at https://derobasegroup.com/i
Thread Class:
2a single mounting facility
Thread Direction:
Right-hand single mounting facility
Overall Length:
0.938 inches
Overall Height:
1.406 inches
Overall Width:
0.734 inches
Case Material:
Plastic
Environmental Protection:
Dustproof
Fragility Factor:
Moderately rugged
Contact Material:
Silver
Contact Surface Treatment:
Gold
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
1.0 kilohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
1 threaded stud single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
0.968 cubic inches
Thready Qty Per Inch (tpi):
48 single mounting facility
Thread Size:

Tillead Size

0.099 inches single mounting facility

NSN 5945-01-081-5478

Electromagnetic Relay - Page 2 of 2



Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Operating Current Rating And Type:

9.4 milliamperes dc single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

3.0 amperes ac resistive load and 3.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Energizing Element Power Rating:

85.0 milliwatts

Precious Material And Location:

Contacts silver and contact surfaces gold

Precious Material:

Silver and gold

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

8 quick disconnect, male all functions

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300