## NSN 5945-01-083-1621

Electromagnetic Relay - Page 1 of 2

1.446 inches single mounting facility

Overall Length: 1.718 inches

**Overall Height:** 



View Online at https://aerobasegroup.com/nsn/5945-01-083-1621

**Center To Center Distance Between Mounting Facilities Parallel To Length:** 

| 1.280 inches   |
|--|
| Overall Width:   |
| 0.465 inches   |
| Mounting Slot Width:   |
| 0.150 inches single mounting facility  |
| Case Material:   |
| Metal  |
| Environmental Protection:  |
| Hermetic   |
| Fragility Factor:  |
| Moderately rugged  |
| Frequency In Hertz:  |
| 400.0  |
| Winding Quantity:  |
| 1  |
| Purpose For Which Designed:  |
| General  |
| Coil Quantity:   |
| 1  |
| Duty Type:   |
| Continuous   |
| Arc Quenching Method:  |
| Air  |
| Mounting Facility Type And Quantity:   |
| 2 slotted hole single mounting facility  |
| a  |
| Storage Type:  |
| Storage Type: General purpose warehouse  |
|  |
| General purpose warehouse  |
| General purpose warehouse  Cubic Measure:  |
| General purpose warehouse  Cubic Measure:  1.022 cubic inches  |
| General purpose warehouse  Cubic Measure:  1.022 cubic inches  Mounting Facility Pattern:  |
| General purpose warehouse  Cubic Measure:  1.022 cubic inches  Mounting Facility Pattern:  In-line single mounting facility  |
| General purpose warehouse  Cubic Measure:  1.022 cubic inches  Mounting Facility Pattern:  In-line single mounting facility  Nonpile-up Main Contact Arrangement:  |
| General purpose warehouse  Cubic Measure:  1.022 cubic inches  Mounting Facility Pattern:  In-line single mounting facility  Nonpile-up Main Contact Arrangement:  2 pole, double throw, one position momentary  |
| General purpose warehouse  Cubic Measure:  1.022 cubic inches  Mounting Facility Pattern: In-line single mounting facility  Nonpile-up Main Contact Arrangement:  2 pole, double throw, one position momentary  Time Delay:  |
| General purpose warehouse  Cubic Measure:  1.022 cubic inches  Mounting Facility Pattern: In-line single mounting facility  Nonpile-up Main Contact Arrangement:  2 pole, double throw, one position momentary  Time Delay:  0.01 seconds fixed operate and release time |

## NSN 5945-01-083-1621

Electromagnetic Relay - Page 2 of 2



## Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac lamp load and 2.0 amperes dc lamp load

**Main Contact Maximum Voltage Rating In Volts:** 

115.0 ac and 28.0 dc

**Terminal Type And Quantity:** 

8 pin all functions

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_\_

Demilitarization:

No

Fiig:

A03300