

View Online at <https://aerobasegroup.com/nsn/5945-01-085-0593>

Thread Class:

2b plate coupling facility hole

Body Style:

Double ended actuator

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.625 inches

Body Diameter:

1.875 inches

Body Height:

1.203 inches

Case Material:

Steel, corrosion resisting

Case Surface Treatment:

Cadmium

Environmental Protection:

Dustproof

Actuator Diameter:

0.250 inches

Inclosure Type:

Fully enclosed

Magnetic Coil Quantity:

1

Electrical Resistance:

38.00 ohms

Duty Type:

Continuous

Terminal Location:

Circumference

Voltage Rating In Volts:

24.0 dc

Mounting Facility Type And Quantity:

2 threaded stud

Torque Rating And Type:

0.45 inch-pounds starting

Thready Qty Per Inch (tpi):

32 plate coupling facility hole

Actuator Stroke Type:

Rotary

Power Takeoff Connection Type:

Plate coupling

Energizing Stroke Maximum Length:

0.500 inches

Plate Coupling Facility And Quantity:

3 threaded hole

Plate Coupling Facility Diameter:

1.688 inches

Plate Coupling Facility Radius:

1.126 inches

Plate Coupling Facility Center To Center Spacing In Deg:

120.0

Thread Size:

0.164 inches mounting facility stud

Mounting Facility Pattern:

Two position in-line

Rotation Direction And Energizing Stroke In Angular Deg:

67.5 counterclockwise

Special Features:

Surface treatment document and classification: baqq-p-416, type 2, class 3

Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification single treatment response

Thread Series Designator:

Unc plate coupling facility hole

Terminal Type And Quantity:

2 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A134a0