

View Online at <https://aerobasegroup.com/nsn/5945-01-085-0593>

**Thread Class:**

2b plate coupling facility hole

**Body Style:**

Double ended actuator

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.625 inches

**Body Diameter:**

1.875 inches

**Body Height:**

1.203 inches

**Case Material:**

Steel, corrosion resisting

**Case Surface Treatment:**

Cadmium

**Environmental Protection:**

Dustproof

**Actuator Diameter:**

0.250 inches

**Inclosure Type:**

Fully enclosed

**Magnetic Coil Quantity:**

1

**Electrical Resistance:**

38.00 ohms

**Duty Type:**

Continuous

**Terminal Location:**

Circumference

**Voltage Rating In Volts:**

24.0 dc

**Mounting Facility Type And Quantity:**

2 threaded stud

**Torque Rating And Type:**

0.45 inch-pounds starting

**Thready Qty Per Inch (tpi):**

32 plate coupling facility hole

**Actuator Stroke Type:**

Rotary

**Power Takeoff Connection Type:**

Plate coupling

**Energizing Stroke Maximum Length:**

0.500 inches

**Plate Coupling Facility And Quantity:**

3 threaded hole

**Plate Coupling Facility Diameter:**

1.688 inches

**Plate Coupling Facility Radius:**

1.126 inches

**Plate Coupling Facility Center To Center Spacing In Deg:**

120.0

**Thread Size:**

0.164 inches mounting facility stud

**Mounting Facility Pattern:**

Two position in-line

**Rotation Direction And Energizing Stroke In Angular Deg:**

67.5 counterclockwise

**Special Features:**

Surface treatment document and classification: baqq-p-416, type 2, class 3

**Surface Treatment Specification:**

Qq-p-416, type 2, class 3 federal specification single treatment response

**Thread Series Designator:**

Unc plate coupling facility hole

**Terminal Type And Quantity:**

2 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A134a0