NSN 5945-01-087-0165

Electromagnetic Relay - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5945-01-087-0165 | |
|---|---|
| Overall Length: | |
| 1.180 inches | |
| Center To Center Distance Between Mounting Facilities Parallel To Length | : |
| 0.995 inches single mounting facility and 1.005 inches single mounting facility | |
| Center To Center Distance Between Mounting Facilities Parallel To Width: | |
| 0.123 inches single mounting facility and 0.127 inches single mounting facility | |
| Overall Height: | |
| 1.108 inches | |
| Overall Width: | |
| 0.400 inches | |
| Environmental Protection: | |
| Dustproof | |
| Unthreaded Mounting Hole Diameter: | |
| 0.096 inches single mounting facility and 0.100 inches single mounting facility | |
| Contact Material: | |
| Silver | |
| Winding Quantity: | |
| 1 | |
| Coil Quantity: | |
| 1 | |
| Winding Dc Resistance Rating: | |
| 200.0 ohms single winding | |
| Duty Type: | |
| Continuous | |
| Mounting Facility Type And Quantity: | |
| 4 unthreaded hole single mounting facility | |
| Mounting Facility Pattern: | |
| Rectangular single mounting facility | |
| Nonpile-up Main Contact Arrangement: | |
| 2 pole, double throw, one position momentary | |
| Operating Current Rating And Type: | |
| 32.0 milliamperes dc single winding | |
| Main Contact Load Current Rating At Maximum Rated Voltage: | |
| 3.0 amperes ac resistive load and 3.0 amperes dc resistive load | |
| Main Contact Maximum Voltage Rating In Volts: | |
| 120.0 ac and 28.0 dc | |
| Precious Material And Location: | |
| Contact silver | |

Precious Material: Silver

Terminal Type And Quantity:

8 wire hook all functions

NSN 5945-01-087-0165

Electromagnetic Relay - Page 2 of 2



| _ | | | | | |
|---|---|------------|---|----|----|
| • | n | 0 1 | • | 12 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300