## NSN 5945-01-087-5231

Electromagnetic Relay - Page 1 of 2

14 wire hook all functions



View Online at https://aerobasegroup.com/nsn/5945-01-087-5231

| Thread Class:  |
|--|
| 2a single mounting facility  |
| Overall Length:  |
| 1.375 inches   |
| Center To Center Distance Between Mounting Facilities Parallel To Width:                                 |
| 0.500 inches single mounting facility  |
| Overall Height:  |
| 1.952 inches   |
| Overall Width:   |
| 0.968 inches   |
| Environmental Protection:  |
| Hermetic   |
| Winding Quantity:  |
| 1  |
| Coil Quantity:   |
| 1  |
| Winding Dc Resistance Rating:  |
| 600.0 ohms single winding  |
| Duty Type:   |
| Continuous   |
| Mounting Facility Type And Quantity:   |
| 3 threaded stud single mounting facility   |
| Pile-up Main Contact Form Arrangement:   |
| 4c   |
| Thready Qty Per Inch (tpi):  |
| 40 single mounting facility  |
| Thread Size:   |
| 0.112 inches single mounting facility  |
| Mounting Facility Pattern:   |
| Triangle single mounting facility  |
| Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: |
| 1.000 inches single mounting facility  |
| Operating Voltage Rating And Type At Specificationified Temp:  |
| 26.5 volts dc 25 degrees celsius single winding  |
| Main Contact Load Current Rating At Maximum Rated Voltage:   |
| 3.0 amperes ac resistive load and 3.0 amperes dc resistive load  |
| Main Contact Maximum Voltage Rating In Volts:  |
| 115.0 ac and 32.0 dc   |
| Thread Series Designator:  |
| Unc single mounting facility   |
| Terminal Type And Quantity:  |

## NSN 5945-01-087-5231

Electromagnetic Relay - Page 2 of 2



| _ |   |            |   |    |    |
|---|---|------------|---|----|----|
| • | n | <b>0</b> 1 | • | 12 | e: |
|   |   |            |   |    |    |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300