

View Online at <https://aerobasegroup.com/nsn/5945-01-087-7563>

Overall Length:

2.230 inches

Overall Diameter:

0.790 inches

Environmental Protection:

Dustproof

End Application:

Ticonderoga class cg (47); oliver perry class ffg; forrestal class cv; kidd class ddg; radar set, lightweight 3d (an/tps-59); aircraft, b-2 bomber (atb); virginia class cgn (41); milstar system; low altitude navigation and targeting infrared system (lantirn)

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

800.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

1 terminal single mounting facility

Nonpile-up Main Contact Arrangement:

1 pole, double throw, one position momentary

Criticality Code Justification:

Feat

Time Delay:

0.01 seconds fixed operate and release time

Operating Voltage Rating And Type At Specificationified Temp:

32.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

500.0 milliamperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

2000.0 dc

Special Features:

Weapon system essential

Test Data Document:

81349-mil-r-83725 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 tab, solder lug contacts

Specification Data:

81349-mil-r-83725/3 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fig:

A03300