NSN 5945-01-090-8352

Electrical Relay Retainer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5945-01-090-8352

Overall Length: Between 2.078 inches and 2.108 inches Overall Height: Between 0.320 inches and 0.360 inches Overall Width: Between 0.600 inches and 0.640 inches Unthreaded Mounting Hole Diameter: 0.155 inches single mounting facility and 0.161 inches single mounting facility Distance Between Mounting Facility Centers: 1.391 inches single mounting facility single center group and 1.421 inches single mounting facility single center group Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility
Overall Height: Between 0.320 inches and 0.360 inches Overall Width: Between 0.600 inches and 0.640 inches Unthreaded Mounting Hole Diameter: 0.155 inches single mounting facility and 0.161 inches single mounting facility Distance Between Mounting Facility Centers: 1.391 inches single mounting facility single center group and 1.421 inches single mounting facility single center group Mounting Facility Type And Quantity:
Between 0.320 inches and 0.360 inches Overall Width: Between 0.600 inches and 0.640 inches Unthreaded Mounting Hole Diameter: 0.155 inches single mounting facility and 0.161 inches single mounting facility Distance Between Mounting Facility Centers: 1.391 inches single mounting facility single center group and 1.421 inches single mounting facility single center group Mounting Facility Type And Quantity:
Overall Width: Between 0.600 inches and 0.640 inches Unthreaded Mounting Hole Diameter: 0.155 inches single mounting facility and 0.161 inches single mounting facility Distance Between Mounting Facility Centers: 1.391 inches single mounting facility single center group and 1.421 inches single mounting facility single center group Mounting Facility Type And Quantity:
Between 0.600 inches and 0.640 inches Unthreaded Mounting Hole Diameter: 0.155 inches single mounting facility and 0.161 inches single mounting facility Distance Between Mounting Facility Centers: 1.391 inches single mounting facility single center group and 1.421 inches single mounting facility single center group Mounting Facility Type And Quantity:
Unthreaded Mounting Hole Diameter: 0.155 inches single mounting facility and 0.161 inches single mounting facility Distance Between Mounting Facility Centers: 1.391 inches single mounting facility single center group and 1.421 inches single mounting facility single center group Mounting Facility Type And Quantity:
0.155 inches single mounting facility and 0.161 inches single mounting facility Distance Between Mounting Facility Centers: 1.391 inches single mounting facility single center group and 1.421 inches single mounting facility single center group Mounting Facility Type And Quantity:
Distance Between Mounting Facility Centers: 1.391 inches single mounting facility single center group and 1.421 inches single mounting facility single center group Mounting Facility Type And Quantity:
1.391 inches single mounting facility single center group and 1.421 inches single mounting facility single center group Mounting Facility Type And Quantity:
Mounting Facility Type And Quantity:
2 unthreaded hole single mounting facility
Material:
Aluminum alloy 5052
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625 military specification single treatment response
Style Designator:
Rectangular prism
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A062a0
Mil-std (military Standard):
Mil-a-8625 spec.