## NSN 5945-01-091-5598

Electrical Solenoid - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-091-5598

| Thread Class:   |
|---|
| 2a mounting facility stud   |
| Body Style:   |
| Base end actuator   |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.250 inches  |
| Body Diameter:  |
| 1.922 inches  |
| Body Height:  |
| 1.109 inches  |
| Maximum Operating Temp:   |
| 71.0 degrees celsius  |
| Actuator Diameter:  |
| 0.250 inches  |
| Inclosure Type:   |
| Fully enclosed  |
| Magnetic Coil Quantity:   |
| 1   |
| Electrical Resistance:  |
| 11.12 ohms  |
| Duty Type:  |
| Continuous  |
| Terminal Location:  |
| Circumference   |
| Electric Power Rating:  |
| 24.0 watts  |
| Voltage Rating In Volts:  |
| 15.0 dc   |
| Mounting Facility Type And Quantity:                                      |
| 2 threaded stud   |
| Torque Rating And Type:   |
| 1.90 inch-pounds end  |
| Actuator Stroke Type:   |
| Rotary  |
| Power Takeoff Connection Type:  |
| Plain   |
| Energizing Stroke Maximum Length:   |
| 0.055 inches  |
| Thread Size:  |
| 0.164 inches mounting facility stud                                       |
| Mounting Facility Pattern:  |

Two position in-line

## NSN 5945-01-091-5598

Electrical Solenoid - Page 2 of 2

**Fiig:** A134a0



| Rotation Direction And Energizing Stroke In Angular Deg: |
|--|
| 95.0 clockwise   |
| Thread Series Designator:                                |
| Unc mounting facility stud                               |
| Terminal Type And Quantity:                              |
| 2 wire lead  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |