NSN 5945-01-091-9536

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-091-9536

Overall Length:

1.718 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.625 inches single mounting facility

Overall Height:

1.280 inches

Overall Width:

1.025 inches

Mounting Slot Width:

0.150 inches single mounting facility

Case Material:

Metal

Environmental Protection:

Hermetic

Fragility Factor:

Moderately rugged

Winding Quantity:

1

Purpose For Which Designed:

Specific

Coil Quantity:

1

Winding Dc Resistance Rating:

290.0 ohms single winding

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

3 slotted hole single mounting facility

Storage Type:

General purpose warehouse

Features Provided:

Polarized

Cubic Measure:

2.254 cubic inches

Mounting Facility Pattern:

Triangle single mounting facility

Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

Operating Current Rating And Type:

120.0 milliamperes dc single winding

NSN 5945-01-091-9536

Electromagnetic Relay - Page 2 of 2



Criticality Code Justification: Feat **Time Delay:** 0.015 seconds fixed operate and release time Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: 1.421 inches single mounting facility **Operating Voltage Rating And Type At Specificationified Temp:** 28.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes ac lamp load and 2.0 amperes dc lamp load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc **Special Features:** Failure rate level 1 persent per 10, 000 cycles **Precious Material And Location:** Terminal surfaces gold **Precious Material:** Gold **Test Data Document:** 81349-mil-r-83536 specification specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 14 pin all functions **Specification Data:** 81349--83536/15-022m government specification Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A03300 Mil-std (military Standard): Mil-r-6106 spec.