# NSN 5945-01-092-3418

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-092-3418

### **Overall Length:**

1.280 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Width:

0.500 inches single mounting facility

#### **Overall Height:**

0.810 inches

#### **Overall Width:**

0.810 inches

#### Mounting Slot Width:

0.133 inches single mounting facility

#### **Case Material:**

Metal

**Environmental Protection:** 

Hermetic

#### Fragility Factor:

#### Moderately rugged

#### Winding Quantity:

1

**Coil Quantity:** 

1

Winding Dc Resistance Rating:

400.0 ohms single winding

**Duty Type:** 

Continuous

#### Mounting Facility Type And Quantity:

3 slotted hole single mounting facility

#### Storage Type:

General purpose warehouse

#### **Features Provided:**

Polarized and coil voltage suppression

#### **Mounting Facility Pattern:**

Triangle single mounting facility

#### Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

#### **Operating Current Rating And Type:**

81.0 milliamperes dc single winding

#### Time Delay:

0.006 seconds fixed operate and release time

#### Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

1.070 inches single mounting facility

## Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

## NSN 5945-01-092-3418

Electromagnetic Relay - Page 2 of 2



#### Main Contact Load Current Rating At Maximum Rated Voltage:

1.0 amperes ac lamp load and 1.0 amperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

**Precious Material And Location:** 

Terminal surfaces gold

**Precious Material:** 

Gold

#### **Test Data Document:**

81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:** 

14 pin all functions

**Specification Data:** 

81349-mil-r-6106/28 government specification

Shelf Life:

N/a

---

Unit Of Measure:

**Demilitarization:** No

Fiig:

A03300