

View Online at <https://aerobasegroup.com/nsn/5945-01-092-6544>

Overall Length:

2.400 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.375 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches single mounting facility

Overall Height:

3.032 inches

Overall Width:

2.313 inches

Environmental Protection:

Hermetic

Unthreaded Mounting Hole Diameter:

0.148 inches single mounting facility

Winding Quantity:

1

Coil Quantity:

1

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

3 pole, double throw, one position momentary

Time Delay:

0.025 seconds fixed operate time

Nonpile-up Auxiliary Contact Arrangement:

1 pole, double throw, one position momentary

Auxiliary Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

60.0 amperes ac resistive load and 60.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Auxiliary Contact Load Current Rating At Maximum Rated Voltage:

3.0 amperes ac resistive load and 3.0 amperes dc resistive load

Test Data Document:

81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

9 threaded stud contacts

Specification Data:

81349-mil-r-6106/9 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300