

View Online at <https://aerobasegroup.com/nsn/5945-01-093-5176>

Overall Length:

2.440 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.000 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches single mounting facility

Overall Height:

3.130 inches

Overall Width:

2.440 inches

Environmental Protection:

Hermetic

Unthreaded Mounting Hole Diameter:

0.170 inches single mounting facility

Winding Quantity:

2

Coil Quantity:

2

Winding Dc Resistance Rating:

200.0 ohms all windings

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Mounting Facility Pattern:

Rectangular single mounting facility

Operating Current Rating And Type:

190.0 milliamperes dc all windings

Time Delay:

0.035 seconds fixed operate time

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius all windings

Main Contact Load Current Rating At Maximum Rated Voltage:

50.0 amperes ac resistive load and 50.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Test Data Document:

81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

13 threaded stud all functions

Specification Data:

96906-ms27750 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300

Mil-std (military Standard):

Mil-r-6106 spec.