NSN 5945-01-093-6233

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-093-6233
Overall Length:
1.320 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.070 inches single mounting facility
Overall Height:
0.597 inches
Overall Width:
0.410 inches
Mounting Slot Width:
0.120 inches single mounting facility
Environmental Protection:
Dustproof
Winding Quantity:
1
Coil Quantity:
1
Winding Dc Resistance Rating:
700.0 ohms single winding
Duty Type:
Continuous
Mounting Facility Type And Quantity:
2 slotted hole single mounting facility
Features Provided:
Polarized
Mounting Facility Pattern:
In-line single mounting facility
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Operating Voltage Rating And Type At Specificationified Temp:
26.5 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
300.0 milliamperes ac resistive load and 2.0 amperes dc resistive load
Main Contact Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Test Data Document:
81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

8 printed circuit all functions

Specification Data:

81349-mil-r-39016/6 government specification

Shelf Life:

N/a

NSN 5945-01-093-6233

Electromagnetic Relay - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A03300