NSN 5945-01-096-3098

Electromagnetic Relay - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5945-01-096-3098 |
|---|
| Overall Length: |
| 1.718 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.446 inches single mounting facility |
| Overall Height: |
| 0.525 inches |
| Overall Width: |
| 1.010 inches |
| Mounting Slot Width: |
| 0.150 inches single mounting facility |
| Case Material: |
| Metal |
| Environmental Protection: |
| Hermetic |
| Fragility Factor: |
| Moderately rugged |
| Winding Quantity: |
| 1 |
| Purpose For Which Designed: |
| General |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 320.0 ohms single winding |
| Duty Type: |
| Continuous |
| Arc Quenching Method: |
| Air |
| Mounting Facility Type And Quantity: |
| 2 slotted hole single mounting facility |
| Storage Type: |
| General purpose warehouse |
| Cubic Measure: |

0.910 cubic inches

Mounting Facility Pattern:

In-line single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Criticality Code Justification:

Feat

Time Delay:

0.01 seconds fixed operate and release time

NSN 5945-01-096-3098

Electromagnetic Relay - Page 2 of 2



| Operating | Voltage | Rating | And | Type At | Specif | icationified | Temp: |
|-----------|---------|--------|-----|---------|--------|--------------|-------|
| | | | | | | | |

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac lamp load and 2.0 amperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Special Features:

Failure rate level 0.5 percent per 1000 operations

Test Data Document:

81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

8 wire hook all functions

Specification Data:

96906-ms27401 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300

Mil-std (military Standard):

Mil-r-6106 spec.