# NSN 5945-01-101-7675

Electromagnetic Relay - Page 1 of 2

1.497 inches single mounting facility

Overall Length: 1.702 inches

**Overall Height:** 



View Online at https://aerobasegroup.com/nsn/5945-01-101-7675

**Center To Center Distance Between Mounting Facilities Parallel To Length:** 

| 1.616 inches                                 |  |
|--|--|
| Overall Width:                               |  |
| 0.847 inches                                 |  |
| Mounting Slot Width:                         |  |
| 0.138 inches single mounting facility        |  |
| Environmental Protection:                    |  |
| Dustproof                                    |  |
| Fragility Factor:                            |  |
| Moderately rugged                            |  |
| Contact Material:                            |  |
| Silver                                       |  |
| Contact Surface Treatment:                   |  |
| Gold flash                                   |  |
| Frequency In Hertz:                          |  |
| 60.0   |  |
| Winding Quantity:                            |  |
| 1  |  |
| Purpose For Which Designed:                  |  |
| General                                      |  |
| Coil Quantity:                               |  |
| 1  |  |
| Duty Type:                                   |  |
| Continuous                                   |  |
| Arc Quenching Method:                        |  |
| Air  |  |
| Mounting Facility Type And Quantity:         |  |
| 2 slotted hole single mounting facility      |  |
| Storage Type:                                |  |
| General purpose warehouse                    |  |
| Features Provided:                           |  |
| Polarized                                    |  |
| Cubic Measure:                               |  |
| 2.329 cubic inches                           |  |
| Mounting Facility Pattern:                   |  |
| In-line single mounting facility             |  |
| Nempile up Main Contact Assensements         |  |
| Nonpile-up Main Contact Arrangement:         |  |
| 4 pole, double throw, one position momentary |  |

## NSN 5945-01-101-7675

Electromagnetic Relay - Page 2 of 2



| I IIIIe Delay. | Time | Del | lay: |
|----------------|------|-----|------|
|----------------|------|-----|------|

0.02 seconds fixed release time

### **Operating Voltage Rating And Type At Specificationified Temp:**

1.2 volts ac 25 degrees celsius all windings and 0.9 volts dc 25 degrees celsius all windings

### **Precious Material And Location:**

Contact silver and contact surface gold

**Precious Material:** 

Gold and silver

### **Terminal Type And Quantity:**

14 tab, solder lug all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300