

View Online at <https://aerobasegroup.com/nsn/5945-01-102-0162>

**Thread Class:**

2a mounting facility stud

**Body Style:**

Base end actuator

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.875 inches

**Body Diameter:**

1.310 inches

**Body Height:**

0.875 inches

**Case Material:**

Metal

**Case Surface Treatment:**

Any acceptable

**Actuator Length:**

0.406 inches

**Actuator Diameter:**

0.187 inches

**Inclosure Type:**

Fully enclosed

**Magnetic Coil Quantity:**

1

**Duty Type:**

Continuous

**Terminal Location:**

Circumference

**Voltage Rating In Volts:**

29.0 dc

**Mounting Facility Type And Quantity:**

2 threaded stud

**Torque Rating And Type:**

0.23 inch-pounds starting

**Thready Qty Per Inch (tpi):**

40 mounting facility stud

**Actuator Stroke Type:**

Rotary

**Power Takeoff Connection Type:**

Plate coupling

**Plate Coupling Facility And Quantity:**

3 threaded hole

**Plate Coupling Facility Center To Center Spacing In Deg:**

120.0

**Thread Size:**

0.125 inches mounting facility stud

**Mounting Facility Pattern:**

Two position in-line

**Rotation Direction And Energizing Stroke In Angular Deg:**

18.0 clockwise

**Special Features:**

Lockarm assembly androllpin

**Thread Series Designator:**

Unc mounting facility stud

**Terminal Type And Quantity:**

2 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A134a0