NSN 5945-01-102-5175

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-102-5175
Overall Length:
1.718 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.396 inches single mounting facility and 1.446 inches single mounting facility
Overall Height:
1.280 inches
Overall Width:
0.525 inches
Mounting Slot Width:
0.150 inches single mounting facility
Environmental Protection:
Hermetic
Winding Quantity:
1
Coil Quantity:
1
Winding Dc Resistance Rating:
320.0 ohms single winding
Duty Type:
Continuous
Mounting Facility Type And Quantity:
2 slotted hole single mounting facility
Mounting Facility Pattern:
In-line single mounting facility
Nonpile-up Main Contact Arrangement:
1 pole, double throw, one position momentary
Operating Current Rating And Type:
110.0 milliamperes dc single winding
Time Delay:
0.01 seconds fixed operate and release time
Operating Voltage Rating And Type At Specificationified Temp:
28.0 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
25.0 amperes ac resistive load and 25.0 amperes dc resistive load
Main Contact Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Special Features:
Permanent magnet drive
Precious Material And Location:
Terminal surface gold
Precious Material:

Gold

NSN 5945-01-102-5175

Electromagnetic Relay - Page 2 of 2



Test Data Document:

81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

5 pin all functions

Specification Data:

81349-mil-r-6106/19 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300